

Aquastop Flangia

Elastic NBR seal for pipes and drains, to be used prior to laying of ceramic, porcelain tiles and natural stone. Applied by cold bonding.

Practical and fast to apply with Aquastop Nanoflex® and all Aquastop waterproofing products, Aquastop Flangia guarantees continuous waterproofing even around drain outlets and through elements.



PRODUCT STRENGTHS

- High elasticity
- For internal and external use
- Ideal for bonding with Aquastop Nanoflex® membrane, Nanodefense® Eco and all Aquastop waterproofing products
- Guaranteed waterproofing of all types of non-structural fractionizing and connection joints
- Central core in breathable NBR and resistant to basic environments

AREAS OF USE

Use

Waterproof sealing of water/electrical systems, through elements and drains on external surfaces (balconies, terraces, flat roofs) and in damp environments (kitchens, shower cubicles, bathrooms, saunas).

Do not use

For visible applications.

INSTRUCTIONS FOR USE

Preparation of substrates

See the technical data sheets of the waterproofing products used for bonding.

Preparation

The seal is ready for use. Directly bond overlapping sections on-site using Aquastop Nanoflex®, Nanodefense® Eco or Kerakoll waterproofing products from the Aquastop range. For Aquastop Flangia 350x350 make an opening according to the diameter of the drainage outlet to be waterproofed prior to laying.

Application

Aquastop Flangia is applied on the floor (350x350) to create a waterproof joint with floor drains and on the wall (120x120) to create a waterproof joint for passage of water/electrical pipes. To bond Aquastop Flangia apply the waterproofing product on the previously prepared substrate using a spreader, insert Aquastop Flangia into the drain or pipe to be waterproofed with the mesh side facing down, then press firmly onto the waterproofing layer while still wet. When laying the second coat of the waterproofing product, completely cover Aquastop Flangia so that it is entirely embedded in the waterproofing layer.

TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	green tape
Shelf life	≈ 24 months
Nature of material	thermoplastic NBR
Application temperature range	from -40 °C to +100 °C

Aquastop Flangia 120x120:

- Pack	20 pcs boxes.
- Dimensions	≈ 120x120 mm
- Thickness	≈ 0.6 mm

Aquastop Flangia 350x350:

- Pack	10 pcs boxes.
- Dimensions	≈ 350x350 mm
- Thickness	≈ 0.8 mm

WARNING

- **Product for professional use**
- abide by any standards and national regulations
- protect the tape once laid from being damaged at the building site
- the product is an item according to the definitions of the EC Regulation No. 1907/2006 and therefore does not require a Safety Data Sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com

The Rating classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in April 2021; please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



KERAKOLL
The GreenBuilding Company

KERAKOLL S.p.a.
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy
Tel +39 0536 816 511 - Fax +39 0536 816 581
info@kerakoll.com - www.kerakoll.com